

Ultracell®


'Quality in Every Language'

UC150-12


12V 150Ah (C₁₀)

12V 175Ah (C₁₀₀)

Deep Cycle Series



Technical Dimensions (mm)




Image



Terminal Dimensions (mm)

Standard Terminal: F11



Technical Specification

Output	Nominal Voltage Nominal Capacity (10HR)	12V 150Ah
Terminal Type	Standard Terminal	F11
Container Material	Standard Option Flame Retardant Option (FR)	ABS ABS (UL94:VO)
Rated Capacity	(100HR 1.80V/cell, 25°C) (20HR 1.80V/cell, 25°C) (10HR 1.80V/cell, 25°C) (5HR 1.75V/cell, 25°C) (3HR 1.75V/cell, 25°C) (1HR 1.60V/cell, 25°C)	172.0Ah/1.72A 160.8 Ah/8.04A 150.0 Ah/15.0A 131.6 Ah/26.3A 119.3 Ah/39.8A 96.9 Ah/96.9A
Max Discharge Current	1500A (5s)	
Internal Resistance	Approx 2.5mΩ	
Discharge Characteristics	Operating Temp Range	Discharge: -15 ~ 50°C Charge: 0 ~ 40°C Storage: -15 ~ 40°C
	Nominal Operating Temp Range	25 ± 3°C
	Cycle Use	Initial Charging Current less than 45A. Voltage 14.4V ~ 15.0V @ 25°C Temp. Coefficient -30mV/°C
	Standby Use	Initial Charging Current less than 45A. Voltage 13.5V ~ 13.8V @ 25°C Temp. Coefficient -20mV/°C
	Capacity Affected by Temperature	40°C 103% 25°C 100% 0°C 86%
Design Floating Life at 20°C	10 Years	

Self Discharge

Ultracell[®] UC batteries may be stored for up to 6 months at 25°C and then a refresh charge is required. For higher temperatures the time intervals will be shorter.


Constant Current Discharge / Constant Power Discharge At 25°C (Amperes & Watts/Cell)

A = Amperes W = Watts


F.V/TIME	10 min	15 min	20 min	30 min	45 min	60 min	2 hours	3 hours	4 hours	5 hours	6 hours	8 hours	10 hours	20 hours
A	W	A	W	A	W	A	W	A	W	A	W	A	W	A
1.85V/cell	219.6 409.8	184.8 348.4	161.5 307.7	116.2 223.3	92.3 178.5	74.9 145.4	46.5 90.7	36.3 70.9	29.4 57.5	23.9 46.9	20.8 41.1	17.0 33.6	14.2 28.0	7.97 15.9
1.80V/cell	280.6 516.6	223.3 414.7	190.9 358.2	137.1 260.3	107.3 205.9	83.9 161.9	50.8 98.3	39.0 75.9	31.4 61.1	25.6 50.2	22.3 44.0	18.0 35.6	15.0 29.7	8.04 16.1
1.75V/cell	308.3 560.6	243.9 448.6	205.3 382.2	142.3 268.9	111.4 212.7	87.8 168.7	52.7 101.7	39.8 77.1	32.1 62.4	26.3 51.4	23.0 45.1	18.3 36.2	15.2 30.0	8.12 16.2
1.70V/cell	336.1 602.5	260.4 475.4	215.8 399.4	148.2 278.8	115.8 220.6	90.5 173.6	54.8 105.5	40.9 79.0	32.9 63.9	27.0 52.6	23.4 46.0	18.6 36.7	15.3 30.2	8.27 16.5
1.65V/cell	362.7 645.6	276.9 502.2	229.2 422.3	156.3 292.8	118.7 225.2	93.6 178.8	56.3 108.1	42.6 82.2	34.1 65.9	27.7 54.0	23.9 46.9	18.9 37.2	15.6 30.8	8.37 16.7
1.60V/cell	393.8 689.0	296.1 530.7	244.2 445.2	165.0 306.0	123.8 232.6	96.9 183.7	58.2 111.1	43.9 84.3	35.1 67.7	28.6 55.5	24.5 47.8	19.1 37.5	15.8 31.1	8.42 16.8




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Cycle Life in Relation to Depth of Discharge



General Relation of Capacity vs. Storage Time



Effects of Temperature on Long Term Float Life



General Relation of Capacity vs. Storage Time (Notes)

- A) No supplementary charge required.
(Carryout supplementary charge before use if 100% capacity is required.)
- B) Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
 3. Charged for 8 ~ 10 hours at limited current 0.05 CA.
- C) Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

